



## SPECIFICATIONS

<b>Weight</b>	Approx. 10.2 kg (Approx. 22.5 lb)
<b>Accessory</b>	Camera cable (Approx. 0.6 m)
<b>Power Supply/Power Consumption</b>	AC 120 V (60 Hz), AC 220 to 240 V (50/60 Hz) / 145 W
<b>Applicable Lens</b>	Standard equipment (removable)
<b>Dimensions (W x H x D) (Pan-Tilt Head only, Excluding Protrusions)</b>	315 mm x 534 mm x 188 mm (12-3/8 inches x 21 inches x 7-3/8 inches)
<b>Maximum Load (Including with a Camera, a Lens and a Teleprompter)</b>	Approx. 8 kg (Approx. 17.6 lb)
<b>Pan/Tilt Angle (Maximum Pan/Tilt Speed)</b>	Pan Approx. $\pm 200^\circ$ (90°/s) Tilt Approx. $\pm 150^\circ$ (90°/s)
<b>Stop Accuracy</b>	under $\pm 30$ arcseconds (0.008°)
<b>Maximum Control Distance (when using AW-RP120G/AW-RP50)</b>	1500 m (when using the protocol converter AW-IF400G*)
<b>Interface RS232C</b>	-
<b>Maximum Preset Memories</b>	50
<b>Teleprompter Output</b>	Standard equipment
<b>AC Adaptor/Power Cable</b>	AC adaptor built in (power cable (2 m) included)

URL: <https://business.panasonic.ru/professional-camera/AW-PH400>

## CONTACT

Web: <https://business.panasonic.ru/professional-camera/contact-us>